

2.4GHz 300Mbps In-wall Access Point

WIS-WM2300

(((**2.4**GHz)))



Product Overview

WIS-WM2300 is a 300Mbps wireless access point based on 802.11b/g/n technology. It is perfectly designed in fashion and compact case and can be easily installed in existing wallplate. Featuring two Ethernet ports and one RJ11 port, WIS-WM2300 can provide both wireless and wired connection for PC and IP Phone. It is a cost-effective and good-user-experience choice for hotel, school, stylish houses, and MDUs (Multi-Dwelling Units).

WIS-WM2300 In-wall access point avoids channels conflict when guests and roomers connect to the Internet as its lowest RF output adjustable to match every room. It enhances every user's experiences with unique and exclusive Internet access and also provides wireless security with WEP and WPA/WPA2 encryption.

Features and Benefits

- Compliant with 802.11n/g/b, speed up to 300Mbps
- Integrated antenna and tx power adjustable
- Small, compact size, easy to install into existing wallplate
- Built in 2*10/100 Base-T Ethernet ports and one RJ11 telephone port
- Up to 4 Multiple SSID
- Supports standard 802.3af POE(48VDC)
- Supports QoS: Traffic Control & WMM
- Supports MAC & IP Address Filter
- Supports mass management with Wisnetworks controller

Specification

> Radio

- 802.11b/g/n radio (Atheros 600MHz)
- Speed up to 300 Mbps
- Frequency Range: 2.4-2.4835GHz
- Tx Power up to 20dBm

> Antenna

- 2*3dBi internal omni-directional antenna

> Interfaces

- 1x 10/100Base-T Ethernet (RJ45 with 48V PoE)
- 2x 10/100Base-T Ethernet
- 1x RJ11 Telephone port
- Reset

>Physical Parameters

- Dimension: 86*86*32mm
- Weight: 0.2kg
- Working Temp: 0 ~ 50°C
- Storage Temp: -20 ~70°C
- Working Humidity: 10%~95% non-condensing

> Management

- Web Interface
- CLI (Telnet)
- Ping Watchdog
- Center Mass Management Tool

>Security

- Integrated Firewall
- WPA/WPA2;WPA-PSK/WPA2-PSK (AES/TKIP) Encryption; 64/128-bit WEP;
- Hidden SSID
- MAC / IP Address Filtering

>Network Mode

- Access Point, Fat/Fit AP
- SOHO Router

> Power

- 48VDC, 0.2A
- Power Consumption: 3W

>Warranty

- 2 Year

>Certification

- CE, RoHS

>Package content

- WIS-WM2300
- Quick Setup Guide
- Mounting Kits

